

Nominal Diameter

7,4 = 43 mm²

Rectus Series

95

Low Pressure

**Technical Description**

This coupling system has been developed specifically for the area of breathing protection. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Additional safety locking system. This safety lock prevents unintentional disconnection. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked. Profile cannot be interconnected with the 96KS series. Tested according EN 139 standard.

Dust Protections  (P. 319) for Coupling Part.-No. SK23S

Working Temperature*
-20°C up to +100°C (NBR) depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.




KS Breathing Air

Working Pressure**

35 bar
** maximum static working pressure with safety factor 4 to 1.

Material



Coupling: Brass / Stainless Steel or Brass nickel plated
Plug: Steel nickel plated
Seals: NBR

Flow diagrams



Couplings – with valve




Series 95KS

Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	19	61	12		23			nickel plated	95KSAK13BPN
	R 1/4	19	61	12		23			Stainless Steel	95KSAK13RPN
	R 3/8	19	60	12		23			nickel plated	95KSAK17BPN
	R 3/8	19	60	12		23			Stainless Steel	95KSAK17RPN
	R 1/2	22	61	17		23			nickel plated	95KSAK21BPN
	R 1/2	22	61	17		23			Stainless Steel	95KSAK21RPN
	G 1/4	19	56	10		23			nickel plated	95KSIW13BPN
	G 1/4	19	56	10		23			Stainless Steel	95KSIW13RPN
	G 3/8	19	55	9		23			nickel plated	95KSIW17BPN
	G 3/8	19	55	9		23			Stainless Steel	95KSIW17RPN
 <p>Female Thread</p>	G 1/2	24	58	12		23			nickel plated	95KSIW21BPN
	G 1/2	24	58	12		23			Stainless Steel	95KSIW21RPN
	6 mm	19	74	25		23			nickel plated	95KSTF06BPN
	7 mm	20	77	22		23			nickel plated	95KSTF07BPN
	8 mm	19	74	25		23			nickel plated	95KSTF08BPN
	9 mm	19	74	25		23			nickel plated	95KSTF09BPN
	9 mm	19	74	25		23			Stainless Steel	95KSTF09RPN
	10 mm	19	74	25		23			nickel plated	95KSTF10BPN
	10 mm	19	74	25		23			Stainless Steel	95KSTF10RPN
	13 mm	19	74	25		23			nickel plated	95KSTF13BPN



Plugs – without valve

Series 95KS

Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number	
 <p>Male Thread</p>	R 1/4	14	38,5	12						95SSAK13MXN	
	R 3/8	17	38,5	12						95SSAK17MXN	
 <p>Female Thread</p>	G 1/4	17	33	9						95SSIW13MXN	
	G 3/8	19	33	9						95SSIW17MXN	
 <p>Hose Barb</p>	6 mm		47,5	25		14				95SSTF06MXN	
	9 mm		47,5	25		14				95SSTF09MXN	
	10 mm		47,5	25		14				95SSTF10MXN	

⚠ Please consider our security advices on the pages 12/13 ⚠