

Nominal Diameter

7,8 = 48 mm²

Rectus Series

1600**Other designs in series 1600**


The following other designs can be found from page:

► Safety Self-Venting P. 294

Technical Description

Rectus Tema premium industrial coupling 3/8" with European standard profile. Suitable for compressed air applications with greater than average air consumption.

Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop.

Dust Protections  (P. 319)

for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S

Working Temperature*

-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with safety factor 4 to 1.

Material


Coupling: Brass nickel plated,
Steel QPQ treated

Plug: Steel zinc plated

Seals: NBR

Interchangeability

- Rectus 25 + 26
- Rectus 1625
- Cejn 320
- JWL 520 + JWL 530
- various German Products

Flow diagrams**Air**



Coupling – with valve

Series 1600KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/4	19		65	12		23				1600KAAK13SPN
	R 3/8	19		65	12		23				1600KAAK17SPN
	R 1/2	22		59,5	17		23				1600KAAK21SPN
<p>Female Thread</p>	G 1/4	19		59	9		23				1600KAIW13SPN
	G 3/8	19		59	9		23				1600KAIW17SPN
	G 1/2	24		62	12		23				1600KAIW21SPN
<p>Hose Barb</p>	6 mm	19		80	25		23				1600KATF06SPN
	8 mm	19		80	25		23				1600KATF08SPN
	9 mm	19		80	25		23				1600KATF09SPN
	10 mm	19		80	25		23				1600KATF10SPN
	13 mm	19		80	25		23				1600KATF13SPN



Plugs – without valve

Series 25SF

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	R 1/8	13		33	9						25SFAK10SXZ
	R 1/4	14		37	12						25SFAK13SXZ
	R 3/8	17		37	12						25SFAK17SXZ
	R 1/2	22		43	17						25SFAK21SXZ
<p>Female Thread</p>	G 1/8	14		30	7						25SFIW10SXZ
	G 1/4	17		38,5	9						25SFIW13SXZ
	G 3/8	19		39,5	9						25SFIW17SXZ
	G 1/2	24		44	12						25SFIW21SXZ
<p>Hose Barb</p>	6 mm			48	25		12				25SFTF06SXZ
	8 mm			48	25		12				25SFTF08SXZ
	9 mm			48	25		12				25SFTF09SXZ
	10 mm			48	25		12				25SFTF10SXZ
	13 mm			48	25		15				25SFTF13SXZ